


Kupplung
0° / 45° / 90°
Aluminium

Female Swivel
0° / 45° / 90°
Aluminium

Part No.	Thread „T“	A max. [mm]	B max. [mm]	SW [mm]
----------	------------	-------------	-------------	---------

Kupplung / Female Swivel S.A.E 37° (JIC/AN)


900-03D	3/8 -24 UNF	32,7	8,5	13,0
900-04D	7/16 -20 UNF	35,3	9,5	14,3
900-06D	9/16 -18 UNF	39,2	16,6	17,4
900-08D	3/4 -16 UNF	45,3	15,5	22,0
900-10D	7/8 -14 UNF	53,5	15,5	25,4
900-12D	1-1/16-12 UN	53,9	15,9	31,6
900-016D	1-5/16-12 UN	59,9	20,4	38,0



Edelstahl auf Anfrage / stainless steel on request


Kupplung Metrisch (DIN) Dichtkegel 60° / Female Swivel Metric (DIN) cone 60°

900-12x1,5	M 12x1,5	33,0	19,0	15,0
900-14x1,5	M 14x1,5	32,9	16,9	19,0
900-18x1,5	M 18x1,5	33,5	15,5	22,0
900-22x1,5	M 22x1,5	33,9	14,9	27,0
900-26x1,5	M 26x1,5	35,9	16,4	32,0
900-30x1,5	M 30x1,5	38,2	17,2	36,0



Kupplung 45° / Female Swivel 45° S.A.E. 37° (JIC/AN)


945-03D	3/8 -24 UNF			
945-04D	7/16-20 UNF			
945-06D	9/16-18 UNF			
945-08D	3/4 -16 UNF			



Edelstahl auf Anfrage / stainless steel on request

Kupplung 90° / Female Swivel 90° S.A.E. 37° (JIC/AN)

990-03D	3/8 -24 UNF	22,0	23,2	13,0
990-04D	7/16-20 UNF	23,2	24,6	14,3
990-06D	9/16-18 UNF	27,2	28,5	17,4
990-08D	3/4 -16 UNF	35,9	37,1	22,0



Edelstahl auf Anfrage / stainless steel on request