


Part No.	Thread „T ₁ “	Thread „T ₂ “	Bördel	A [mm]	B [mm]	SW [mm]
----------	--------------------------	--------------------------	--------	--------	--------	---------

Bordwanddurchführung Aluminium / Bulkheads Aluminium
Gewindeloch DIN 74235 Form FL (Bördel F) / Threadhole DIN 74235 Form FL (Flare F)

832-10x1	M 10x1 fem ³	M 10x1 fem ³	F	10,1	16,7	19,0
832-10x1 SS ²	M 10x1 fem ³	M 10x1 fem ³	F	11,1	16,7	19,0
832-10x1-03 D	M 10x1 fem ³	3/8-24 UNF	F	11,3	17,6	19,0
832-10x1-03 SS ²	M 10x1 fem ³	3/8-24 UNF	F	11,3	17,6	19,0
833-10x1	M 10x1 fem ³	M 10x1 fem ³	F	22,0	23,3	
833-10x1-03 D	M 10x1 fem ³	3/8-24 UNF	F	22,0	36,3	
833-10x1-03 D fem	M 10x1 fem ³	3/8-24 UNF fem ³	F	22,0	23,3	
833-10x1-03 Ti ⁴ fem	M 10x1 fem ³	3/8-24 UNF fem ³	F	22,0	23,3	



¹ Alle Gewindelöcher M 10x1 nach DIN 74235 Form FL (Bördel F) / All threadholes M 10x1 according to DIN 74235 Form FL (Flare F)

² SS für Edelstahl / SS for stainless steel

³ Innengewinde / female thread

⁴ Ti für Titan / Ti for titanium