




Part No.	Hose Size	Thread "T"	A max. [mm]	B max. [mm]	C max. [mm]	I max. [mm]	SW <sub>1</sub> [mm]	SW <sub>2</sub> [mm]
----------	-----------	------------	-------------	-------------	-------------	-------------	----------------------	----------------------

**Fitting / Fitting**  
**Edelstahl / Stainless Steel** S.A.E.37° JIC siehe Crimp Fitting 6000 / see crimp fitting 6000

6001-03 SS <sup>3</sup>	6000-03D	3/8 -24 UNF	24,5	8,6		2,3	13,0	13,0
-------------------------	----------	-------------	------	-----	--	-----	------	------

6045-03 SS <sup>1/3</sup>	6000-03D	3/8 -24 UNF	30,0	12,0	21,8	2,3	13,0	11,0
---------------------------	----------	-------------	------	------	------	-----	------	------

6090-03 SS <sup>1/3</sup>	6000-03D	3/8 -24 UNF	30,0	11,1	19,3	2,3	13,0	11,0
---------------------------	----------	-------------	------	------	------	-----	------	------



**Ersatzolive<sup>4</sup> / Spare Olive**

0L-03

**Ersatzsocket / Spare Socket**

So-6000-03SS

<sup>1</sup> Alle Winkelstücke werden aus Gesenkschmiedeteilen gefertigt / All fittings are block forged

<sup>3</sup> SS für Edelstahl / SS for stainless steel

<sup>4</sup> Nach jedem Lösen der Schlaucheinbindung muß die Dichtolive erneuert werden / You have to use a new olive after replacement of hose

**Anschlußarmaturen für Bremsleitung  
Typ RTEC G3**





**Fittings for Brakeline  
Type RTEC G3**



Part No.	Hose Size	Thread "T"	Pos. Angle	A max. [mm]	B max. [mm]	C max. [mm]	I max. [mm]	SW <sub>1</sub> [mm]
----------	-----------	------------	------------	-------------	-------------	-------------	-------------	----------------------

**Fitting / Fitting**  
**Edelstahl / Stainless Steel S.A.E.37° JIC**     siehe Crimp Fitting 6000 / see crimp fitting 6000

6001-03 SS <sup>2</sup> CR	6000-03D	3/8-24 UNF	00°	25,1	8,6		2,3	13,0
6045-03 SS CR	6000-03D	3/8-24 UNF	45°	30,0	12,0	21,8	2,3	13,0
6090-03 SS CR	6000-03D	3/8-24 UNF	90°	30,0	11,1	19,3	2,3	13,0
6001-03 SS male	6000-03D	3/8-24 UNF	00°	18,3	17,0		2,3	14,0



<sup>2</sup> SS für Edelstahl / SS for stainless steel

<sup>5</sup> Vorteil: auch Hohlrauben ohne Verjüngung können verwendet werden / Advantage: You don't have to use waisted banjo bolts